



## WJB銅自潤軸承 (特殊規格尺寸可依圖訂製)

### 特殊銅合金系



### 自潤#500SP 止推墊圈(SPW)

尺寸 (mm)		厚度T					公差 <sup>0</sup> <sub>0.1</sub>			裝配孔			倒角	
內徑 ∅d	外徑 ∅D	3	5	7	8	10	P.C.D	個數	使用埋頭螺栓	a	b			
		SPW	SPW	SPW	SPW	SPW								
10.2	30	<b>-1003</b>					20	2	M3	1.5	0.3			
12.2	40	<b>-1203</b>					28	"	"	2	0.4			
12.2	40	<b>-1203N</b>					無埋頭螺栓孔			"	"			
13.2	40	<b>-1303</b>					28	2	M3	"	"			
14.2	40	<b>-1403</b>					"	"	"	"	"			
15.2	50	<b>-1503</b>					35	"	"	"	"			
16.2	50	<b>-1603</b>					"	"	"	"	"			
16.2	50	<b>-1603N</b>					無埋頭螺栓孔			"	"			
18.2	50	<b>-1803</b>					35	2	M3	"	"			
20.2	50	<b>-2005</b>					"	"	M5	2.5	"			
25.2	55	<b>-2505</b>					40	"	"	"	"			
30.2	60	<b>-3005</b>					45	"	"	"	"			
35.2	70	<b>-3505</b>					50	"	"	"	"			
40.2	80	<b>-4007</b>					60	"	M6	3	0.5			
45.2	90	<b>-4507</b>					70	"	"	"	"			
50.3	100	<b>-5008</b>					75	4	"	4	0.6			
55.3	110	<b>-5508</b>					85	"	"	"	"			
60.3	120	<b>-6008</b>					90	"	M8	5	0.8			
65.3	125	<b>-6508</b>					95	"	"	"	"			
70.3	130	<b>-7010</b>					100	"	"	"	"			
75.3	140	<b>-7510</b>					110	"	"	"	"			
80.3	150	<b>-8010</b>					120	"	"	"	"			
90.5	170	<b>-9010</b>					140	"	M10	"	"			
100.5	190	<b>-10010</b>					160	"	"	"	"			
120.5	200	<b>-12010</b>					175	"	"	"	"			

- 請參考SPB組配。
- 可與SPB合併使用。

訂購型號

SPW -        
          內徑  厚度